Analytical Biochemistry 443 (2013) 169-171

Contents lists available at ScienceDirect

Analytical Biochemistry

journal homepage: www.elsevier.com/locate/yabio





Analytical Biochemistry

Ampornphan Siriviriyanun^a, Toyoko Imae^{a,b,*}, Naoki Nagatani^c

^a Graduate Institute of Applied Science and Technology, National Taiwan University of Science and Technology, Taipei 10607, Taiwan, ROC

^b Department of Chemical Engineering, National Taiwan University of Science and Technology, Taipei 10607, Taiwan, ROC

^c Department of Biotechnology and Applied Chemistry, Faculty of Engineering, Okayama University of Science, Okayama 700-0005, Japan

ARTICLE INFO

Article history: Received 20 June 2013 Received in revised form 29 August 2013 Accepted 4 September 2013 Available online 11 September 2013

Keywords: Poly(amido amine) dendrimer Platinum nanoparticle Multiwalled carbon nanotube Enzyme reaction Electrochemical biosensor Inhibition reaction

ABSTRACT

The presented approach provides the advanced development of effective, rapid, and versatile electrochemical sensors for a small amount of analytes on potential, cheap, and disposable printed chips. The electrocatalytic activity of this biosensor revealed the feasible detection of hydrogen peroxide at low potential (\sim 0.09 V) and the detection of a biocontaminant inhibitor (organophosphorus pesticide) in a wide range of concentrations. This efficiency comes from the chemical immobilization of catalysts (Pt nanoparticles) and electron transfer-enlarging materials (carbon nanotubes) on an electrode. Especially, dendrimers raise the stable conjugation of enzymes (acetylcholinesterase/choline oxidase/peroxidase) as well as nanoparticles and carbon nanotubes on an electrode.

© 2013 Elsevier Inc. All rights reserved.

The utilization of metal-based nanoparticles as an immobilization site for enzymes has been developed for biosensing approaches [1,2]. Platinum nanoparticles (PtNPs) can catalyze excellently an electrochemical reaction on oxidation of H₂O₂, which is generated by the enzymatic reaction [1,3]. Meanwhile, multiwalled carbon nanotubes (MWCNTs) can be employed to modify the working electrode for the enlargement of the electroactive surface area, which leads to an increase in the electron transfer properties of the biosensing system [4]. Electrodes modified by hybrids of carbon nanotubes (CNTs) and metal nanoparticles have been developed for use as fuel-cell catalysts and biosensors [5–8]. A Pt–CNT–glucose biosensor was developed using the incorporation of glucose oxidase (GOx) on a Pt-CNT electrode [6]. Even though this biosensor revealed a high sensitivity toward glucose oxidation, its stability after storage for a few days decreased owing to the release of GOx that is not entrapped within the Pt_{nano}/SiO₂ composite matrix as a binder.

In a previous work, electrodes modified by hybrids of CNTs and PtNPs protected by dendrimers were developed for electrochemical methanol oxidation [8]. In the present work, chemically stable electrochemical biosensors consisting of an electrode loading MWCNTs and PtNPs were developed by the mediation of poly(ami-

* Corresponding author at: Graduate Institute of Applied Science and Technology, National Taiwan University of Science and Technology, Taipei 10607, Taiwan, ROC. *E-mail address:* imae@mail.ntust.edu.tw (T. Imae).

0003-2697/\$ - see front matter @ 2013 Elsevier Inc. All rights reserved. http://dx.doi.org/10.1016/j.ab.2013.09.004 do amine) dendrimer (DEN) as a binder and the immobilization of enzymes on them as shown in Scheme 1. The goal of this study was to test the feasibility of this electrode. Thus, the detection of an organophosphorus pesticide through the inhibition of the acetylcholinesterase (AChE) enzyme reaction was investigated by cyclic voltammetry (CV) to judge the availability of the present sensing system. In the sensors, carbon nanotubes are expected to enlarge the surface area of the working electrode and promote the electron-transfer properties. PtNPs can also intensify the electrontransfer ability in addition to catalytic performance, and dendrimers play a role in the uptake of the redox agent as well as the binder functionality. Thus the CNT/DEN(PtNPs)-loaded electrode possesses high durability and reactivity [8].

Experimental details and tables of results are provided in the Supplementary material. For the electrochemical detection of diazinon oxon (DZN), CNT/DEN(PtNPs) hybrids were fabricated onto a disposable electrochemical printed (DEP) chip with a screenprinted circular glassy carbon (SPCGC) working electrode. The characterization of CNT/DEN(PtNPs) hybrids was reported previously [9]. In addition, it has been reported that the CNT/ DEN(PtNPs)-loaded SPCGC electrode possessed high stability, since DEN(PtNPs) and CNT/DEN(PtNPs) still retained their physical and chemical immobilization on the DEP chips through binders/stabilizers even after 20 cycles of the CV scan [8]. Therefore DEN plays an important role as a stabilizer and binder in CNT/DEN(PtNPs)loaded SPCGC electrodes [8,9]. Successively, enzymes were loaded





Scheme 1. Schematic illustration of preparation of biosensor, loading multiwalled carbon nanotubes, platinum nanoparticles, and enzymes through dendrimer binders.

on the electrode, and the bioactivity of the as-prepared biosensor was investigated by CV. It is well known that AChE plays an important role in cholinergic transmission as a catalyst for the rapid hydrolysis of the neurotransmitter acetylcholine into acetate and choline. The choline is subsequently converted by choline oxidase (ChO), producing hydrogen peroxide in the presence of oxygen [4,5].

The inhibition of AChE activity by DZN can be determined by measuring the redox current of H₂O₂, which is correlated with the concentration of choline produced by AChE. Enzymes were used for the detection of organophosphorus compound in this work, but the activity of the enzymes is affected by the chemical environment (e.g., pH, temperature, ionic strength, and so on). Therefore, for biosensors based on an enzyme system, the sensor activity may also depend on such environments. It has been reported that the optimum pH for ChO enzyme activity is between 7.0 and 8.0 and that for AChE is between 8.0 and 9.0 [10]. It was also found that choline will lose its activity at pH < 6.0, and the hydrolysis of organophosphorus compound was observed at pH > 8.0 [4]. For the case of choline electrochemical biosensors, the choline sensing was carried out in phosphate buffer solution at pH 7.5 [11]. Thus, in view of these reports, electrochemical detection of DZN was carried out in a phosphate buffer solution at pH 7.4 to maintain both the stability and the activity of the AChE, ChO, and peroxidase (POD) enzymes. On the other hand, the inhibition of AChE activity by organophosphorus compound is an irreversible process; when the enzyme is exposed on the organophosphorus compound, the enzyme is inactivated and therefore the sensor can be reused only after an appropriate enzyme reactivation. Thus, biosensors that are low cost and disposable are highly desirable in this application [12,13].

The cyclic voltammograms of an enzyme/CNT/DEN(PtNPs)loaded SPCGC electrode in a 10 mM phosphate buffer (pH 7.4) solution of acetylcholine chloride showed a well-defined anodic oxidation peak at the potential around 0.09 V with an anodic peak current density of 0.12 mA/cm², as seen in Fig. 1, although such peaks were not observed on the electrode without acetylcholine chloride (Fig. 1, control) and without loaded enzymes (Supplementary Fig. S1). This peak might be attributed to the oxidation of H_2O_2 generated from the enzymatic reaction of AChE and ChO [1,2,10,14]. It might be noticed that the peak potential of H₂O₂ oxidation by the present electrode is lower than by an AChE/ChO/CNT electrode (0.50 V) [3]. This indicates that the enzyme/CNT/ DEN(PtNPs)-loaded SPCGC electrode possesses an excellent electrocatalytic activity toward the oxidation of H₂O₂ at low potential, and it might be attributed to the presence of DEN(PtNPs) on this biosensor. The low oxidation potentials reveal an advantage of this electrode, because only low potential is needed for the detection and there is no interference from the other electroactive species in the sample derived from the high applied potential. Meanwhile, a reduction peak around -0.5 V was also observed. This peak is attributed to the reduction of the generated H₂O₂ by POD. Hence, the inhibition of enzyme activity of AChE by DZN can be determined by the decrease in the oxidation or reduction current at 0.09 and -0.5 V, respectively.

With addition of DZN to the solution of acetylcholine chloride, an anodic oxidation peak around 0.09 V shifted to lower potential and decreased in the current density. It can be suggested that the obtained decrease in the anodic current is due to the inhibition of the AChE enzyme activity by DZN, leading to a diminution in the concentration of choline and in the amount of H_2O_2 generated from the enzymatic reaction.

The obtained currents of the anodic oxidation peak were utilized to evaluate the enzyme activity, I_0/I_x , and the inhibition value, $(I_0 - I_x)/I_0$, where I_0 and I_x are taken from current densities in solutions of acetylcholine chloride without and with DZN. The calculated values are listed in Supplementary Table S1 and plotted in Fig. 2a, where the regression values of the linear relations were 0.78 and 0.97 for Na₂PtCl₆ to the amino-terminal group of the dendrimer (M:D) = 0.2:1 and 0.4:1, respectively. It was found that the enzyme activity decreased and, therefore, the inhibition percentage increased with increasing DZN concentration. A linear relationship between the inhibition percentage and the logarithmic DZN concentration covered a wider DZN concentration range below 10 ppm than in the previous report [15]. It can be noted that the enzyme/CNT/DEN(PtNPs)-loaded SPCGC electrode reveals a significant detection performance for DZN based on the inhibition of enzyme reaction at low potential around 0.09 V.

Platinum is very active in the electro-oxidation of H_2O_2 , and a PtNP electrode oxidizes at a lower potential than a Pt bulk electrode. It was observed in Fig. 2a that the detection of H_2O_2 by the enzyme/CNT/DEN(PtNPs)-loaded SPCGC electrode at M:D = 0.4 was higher than at M:D = 0.2. The percentage inhibition at various M:D ratios toward the detection of H_2O_2 in the presence of 0.1 ppm DZN is shown in Fig. 2b (numerical values are listed in Supplementary Table S1). It was observed that the percentage inhibition of AChE activity significantly increased from 15% at



Fig.1. Cyclic voltammograms of enzyme/CNT/DEN(PtNPs)-loaded SPCGC electrodes in a 10 mM phosphate buffer solution (pH 7.4) of acetylcholine chloride. Numerical values denote the concentration of DZN. Control experiment was carried out in 10 mM phosphate-buffered saline (pH 7.4) without acetylcholine chloride.



Fig.2. Plots of % inhibition of acetylcholinesterase enzyme reaction (a) by diazinon oxon using the enzyme/CNT/DEN(PtNPs)-loaded SPCGC electrode at *M*:*D* = 0.2:1 (\bigcirc) and 0.4:1 (\blacksquare) and (b) in the presence of 0.1 ppm diazinon oxon using the enzyme/CNT/DEN(PtNPs)-loaded SPCGC electrode at various *M*:*D* ratios.

M:D = 0.1:1 to 43% at M:D = 0.4:1, although the percentage inhibition decreased at M:D = 0.5:1. The increase in the percentage inhibition of AChE activity against M:D might be due to the promotion of the oxidation of H_2O_2 , which was performed by PtNPs on the electrode. Thus, it could be suggested that the percentage inhibition depends on the amount of PtNPs loaded on the electrode, similar to a previous report [16]. It has been reported that the electrocatalytic activity of the catalyst is influenced by the composition, the content, and the activity efficiency of the electrocatalyst, leading to the required current [17].

In conclusion, the enzyme/CNT/DEN(PtNPs)-loaded SPCGC electrode, which was fabricated using the immobilization of three enzymes (AChE, ChO, and POD) on a CNT/DEN(PtNPs)-loaded SPCGC electrode, showed a desirable electrocatalytic activity on the enzyme reaction toward the oxidation and reduction of H_2O_2 at low potential around 0.09 and -0.5 V, respectively, and the significant detection of a biocontaminant (DZN) based on the inhibition of enzyme reaction in a wide range of DZN concentrations. In addition, the sensitivity of the detection of H_2O_2 by the enzyme/CNT/DEN(PtNPs)-loaded SPCGC electrode depends on the amount of PtNPs loaded on the electrode. This indicates the remarkable sensitivity and the selective detection ability of the present electrode for any kind of target molecule, if an adequate molecular recognition or reaction system is loaded on the electrode. Above all, dendrimers can play a role in not only the binding of CNTs and PtNPs on electrodes but also the stable conjugation of enzymes. Moreover, the DEP chips are adequate for a small amount of analytes and rapid testing. Therefore, the present approach provides the advanced development of an effective and versatile electrochemical sensing system for wide application as biomedical, food, chemical, and environmental sensors.

Acknowledgments

This work was financially supported by the National Taiwan University of Science and Technology, Taiwan, under Grant 100H451201. A.S. gratefully acknowledges the National Taiwan University of Science and Technology, Taiwan, for financial support through a postdoctoral fellowship.

Appendix A. Supplementary data

Supplementary data associated with this article can be found, in the online version, at http://dx.doi.org/10.1016/j.ab.2013.09.004.

References

- [1] A. Guerrieri, F. Palmisano, An acetylcholinesterase/choline oxidase-based amperometric biosensor as a liquid chromatography detector for acetylcholine and choline determination in brain tissue homogenates, Anal. Chem. 73 (2001) 2875–2882.
- [2] R.S. Dey, C.R. Raj, Development of an amperometric cholesterol biosensor based on graphene–Pt nanoparticle hybrid material, J. Phys. Chem. C 114 (2010) 21427–21433.
- [3] H. Yang, Y. Zhu, Glucose biosensor based on nano-SiO₂ and "unprotected" Pt nanoclusters, Biosens. Bioelectron. 22 (2007) 2989–2993.
- [4] M.U. Ahmed, M.M. Hossain, E. Tamiya, Electrochemical biosensors for medical and food applications, Electroanalysis 20 (2008) 616–626.
- [5] W. Lin, F. Lu, J. Wang, Disposable carbon nanotube modified screen-printed biosensor for amperometric detection of organophosphorus pesticides and nerve agents, Electroanalysis 16 (2004) 145–149.
- [6] G. Liu, S.L. Riechers, M.C. Mellen, Y. Lin, Sensitive electrochemical detection of enzymatically generated thiocholine at carbon nanotube modified glassy carbon electrode, Electrochem. Commun. 7 (2005) 1163–1169.
- [7] M. Yang, Y. Yang, Y. Liu, G. Shen, R. Yu, Platinum nanoparticles-doped sol-gel/ carbon nanotubes composite electrochemical sensors and biosensors, Biosens. Bioelectron. 21 (2006) 1125–1131.
- [8] A. Siriviriyanun, T. Imae, Advantages of electrodes with dendrimer-protected platinum nanoparticles and carbon nanotubes for electrochemical methanol oxidation, Phys. Chem. Chem. Phys. 15 (2013) 4921–4929.
- [9] A. Siriviriyanun, T. Imae, Advantages of immobilization of Pt nanoparticles protected by dendrimers on multiwalled carbon nanotubes, Phys. Chem. Chem. Phys. 14 (2012) 10622–10630.
- [10] M. Snejdakova, L. Svobodova, D.P. Nikolelis, J. Wang, T. Hianik, Acetylcholine biosensor based on dendrimer layers for pesticides detection, Electroanalysis 15 (2003) 1185–1191.
- [11] G. Palleschi, M. Bernabei, C. Cremisni, M. Mascini, Determination of organophosphorus insecticides with a choline electrochemical biosensor, Sens. Actuators B 7 (1992) 513–517.
- [12] V. Dounin, A.J. Veloso, H. Schulze, T.T. Bachmann, K. Kerman, Disposable electrochemical printed gold chips for the analysis of acetylcholinesterase inhibition, Anal. Chim. Acta 669 (2010) 63–67.
- [13] S.D. Dzydevich, A. Shel'ga, A.P. Soldatkin, A.M. Nyamsi Hendji, N.J. Renault, C. Matelet, Conductometric biosensors based on cholinesterases for sensitive detection of pesticides, Electroanalysis 6 (1994) 752–758.
- [14] A. Cagnini, I. Palchetti, I. Lionti, M. Mascini, A.T.F. Turner, Disposable ruthenized screen-printed biosensors for pesticides monitoring, Sens. Actuators B 24–25 (1995) 85.
- [15] N. Nagatani, A. Takeuchi, M.A. Hossain, T. Yuhi, T. Endo, K. Kerman, Y. Takamura, E. Tamiya, Rapid and sensitive visual detection of residual pesticides in food using acetylcholinesterase-based disposable membrane chips, Food Control 18 (2007) 914–920.
- [16] T. You, O. Niwa, M. Tomita, S. Hirono, Characterization of platinum nanoparticle-embedded carbon film electrode and its detection of hydrogen peroxide, Anal. Chem. 75 (2003) 2080–2085.
- [17] Y.J. Gu, W.T. Wong, Nanostructure PtRu/MWNTs as anode catalysts prepared in a vacuum for direct methanol oxidation, Langmuir 22 (2006) 11447–11452.